

Specifications

Make Model Drive Chassis	BRANSON 5530 cabin 4WD Rigid	BRANSON 5530 rops 4WD Rigid	BRANSON 6530 cabin 4WD Rigid	BRANSON 6530 rops 4WD Rigid
Standard Specification				
Engine	A2300T2-ATC	A2300T2-ATC	Cummins 3.3	Cummins 3.3
Number Cylinders/cc	4/2286	4/2286	4T/3260	4T3260
Engine Power kw/(hp)	41/55	41/55	48/65	48/65
@ rated speed	2600	2600	2600	2600
Rating Standard	Mfr	Mfr	Mfr	Mfr
PTO				
PTO kw/(hp)	36.5/(47.0)	36.5/(47.0)	43/(57)	43/(57)
Source of Rating	Est	Est	Est	Est
Type	Live	Live	Live	Live
Ground Speed/540E	No/No	No/No	No/No	No/No
Speeds	540/750/1000	540/750/1000	540/750/1000	540/750/1000
Speed Selection Method	Lever	Lever	Lever	Lever
Transmission				
Type	Synchro Shuttle	Synchro Shuttle	Synchro Shuttle	Synchro Shuttle
High-Low/Shuttle	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes
Speeds Forward/Reverse	24/24	24/24	24/24	24/24
Speed Range	0.20-26.0	0.20-26.0	0.20-26.0	0.20-26.0
Clutch Type	Dry	Dry	Dry	Dry
Hydraulic System				
Description	Open Centre	Open Centre	Open Centre	Open Centre
Pump Type	Gear	Gear	Gear	Gear
Max l/min - Pressure kg/cm ²	41.6/160	41.6/160	41.6/160	41.6/160
Remote Outlets Std/Max	2	2	2	2
3 Point Linkage				
Category	1	1	2	2
Draft Sensing	top link	top link	top link	top link
Lift - kg @ Position	1821@BE	1821@BE	1921@BE	1921@BE
Brake Type	Wet Disc	Wet Disc	Wet Disc	Wet Disc
Steering Type	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Tyre Equipment				
Standard Front	9.2-20	9.2-20	11.2-20	11.2-20
Standard Rear	14.9-28	14.9-28	14.9-30	14.9-30
Turf Front	Optional	Optional	Optional	Optional
Turf Rear	Optional	Optional	Optional	Optional
Dimension/Weights				
Minimum Width	1720	1720	1790	1790
Turning Circle (No Brakes)	4153	4153	4000	4000
Dry Shipping Weight (kg)	2441	2309	2640	2432